


ELECTRIC CURTAIN TRACK SYSTEMS



GENERAL NOTES

Dimensions

- Measurements are in mm except where indicated.
- Max. kg relates to fabric incl. accessories.
- Stack size depends on curtain make-up and fabric thickness.
- Distance between gliders max. 80 mm / distance between rollers max. 100 mm.
- Recommended distance floor / fabric: 20 mm.
- In order to determine system height (B), the smallest room height must be taken into account.
- Full functionality may be affected if the curtain touches the profile.

Fitting

- Installation by qualified fitter only.
- Number of brackets and fitting positions / fixing points vary depending on fitting surface, system weight, fabric make-up, screw / fixing type and obstacles.
- Qualified fitter must use appropriate screws / fixings for each situation.
- Profile lip if applicable to be installed to room side.
- Electrical installations must be carried out according to Silent Gliss wiring diagrams and conform to local regulations.
- Check space for cables and plugs!



Child Safety

- All relevant Silent Gliss systems correspond to child safety EN 13120.
- All parties involved must comply with EN 13120.

APPLICATION CHART

PAGE	SYSTEM	OPERATION	DIMENSION	DESIGN	WAVE	← max. →	kg _{max.}
5	SG 5100		S - M			9 m	30 kg
19	SG 5600		S - L			25 m	65 kg

SG 5100



PRODUCT INFORMATION


- **Operation:** motorised
- **Range:** S - M
- **Fitting:** ceiling, wall, recess
- **Colours:** white RAL 9016, black RAL 9005* (*motor in white only), grey+ (+motor, gear drive, glider in white only), special colours possible (recess profile only in white, black or special color)
- **Fabrics:** refer to Silent Gliss fabric collection

Features:

- 2-component (2C) roller technology
- Wave (2C)
- Various control options
- Touch & Go
- Manual override
- Different motor versions
- Bendable
- Bendable recess profile

SYSTEM SPECIFICATIONS

A. SYSTEM DIMENSIONS



Max. curtain weights with 2C rollers / Wave rollers


	3 m	6 m	9 m
	25	30	28
	25	30	28
	25	22	18
	25	22	18
	20	18	13
	20	18	13
	15	13	-
	15	13	-
(kg max.)			

Max. curtain weights with Wave gliders


	3 m	6 m	9 m
	20	20	18
	20	20	18
	18	14	10
	18	14	10
	12	10	8
	12	10	8
	10	9	-
	10	9	-
(kg max.)			

B. PROFILE

Profile and bending information



C. HOW TO MEASURE



A: System width
B: System height
C: Distance between floor and fabric

D. SPECIFICATION TEXT

Silent Gliss SG 5100 Electrically Operated Curtain Track – Option Base (B) Comprises aluminium profile SG 10850 in silver [anodized / white / black] powder coated finish complete and assembled with motor 5190 in white. Includes motor holder set 11464, internal drive belt SG 10825, belt return set SG 10819. Supplied with [2C roller gliders SG 10840 / Wave 2C glider cord 60mm SG 10906 / Wave 2C 80mm glider cord SG 10905 / 2C Wave roller glider cord 60mm SG 10869 / 2C Wave roller glider cord 80mm SG 10852]. Features manual 'Touch and Go' operation and manual override in the event of power failure. Fitted using [top fixed clamps SG 3004 at max. 500mm centres / face fixed with Silent Gliss Smart Fix extension brackets]. Optional recess profile SG 10862 in [white / black]. Operation via wireless wall switch SG 10949.

Silent Gliss SG 5100 Electrically Operated Curtain Track – Option Remote (R). Comprises aluminium profile SG 10850 in silver [anodized / white / black] powder coated finish complete and assembled with motor 5190 in white. Includes motor holder set 11464, internal drive belt SG 10825, belt return set SG 10819. Supplied with [2C roller gliders SG 10840 / Wave 2C glider cord 60mm SG 10906 / Wave 2C 80mm glider cord SG 10905 / 2C Wave roller glider cord 60mm SG 10869 / 2C Wave roller glider cord 80mm SG 10852]. Features manual 'Touch and Go' operation and manual override in the event of power failure. Fitted using [top fixed clamps SG 3004 at max. 500mm centres / face fixed with Silent Gliss Smart Fix extension brackets]. Optional recess profile SG 10862 in [white / black]. Operation via remote wireless control handset SG 10946 and wireless wall switch SG 10949.

Silent Gliss SG 5100 Electrically Operated Curtain Track – Option Timer (T) Comprises aluminium profile SG 10850 in silver [anodized / white / black] powder coated finish complete and assembled with motor 5190 in white. Includes motor holder set 11464, internal drive belt SG 10825, belt return set SG 10819. Supplied with [2C roller gliders SG 10840 / Wave 2C glider cord 60mm SG 10906 / Wave 2C 80mm glider cord SG 10905 / 2C Wave roller glider cord 60mm SG 10869 / 2C Wave roller glider cord 80mm SG 10852]. Features manual 'Touch and Go' operation and manual override in the event of power failure. Fitted using [top fixed clamps SG 3004 at max. 500mm centres / face fixed with Silent Gliss Smart Fix extension brackets]. Optional recess profile SG 10862 in [white / black]. Operation via wireless wall switch SG 10949 and wireless timer SG 11429.


Silent Gliss SG 5100 Electrically Operated Curtain Track – Option Total Control (TC). Comprises aluminium profile SG 10850 in silver [anodized / white / black] powder coated finish complete and assembled with motor 5190 in white. Includes motor holder set 11464, internal drive belt SG 10825, belt return set SG 10819. Supplied with [2C roller gliders SG 10840 / Wave 2C glider cord 60mm SG 10906 / Wave 2C 80mm glider cord SG 10905 / 2C Wave roller glider cord 60mm SG 10869 / 2C Wave roller glider cord 80mm SG 10852]. Features manual 'Touch and Go' operation and manual override in the event of power failure. Fitted using [top fixed clamps SG 3004 at max. 500mm centres / face fixed with Silent Gliss Smart Fix extension brackets]. Optional recess profile SG 10862 in [white / black]. Operation via remote control SG 10946, timer unit SG 11429 and fixed manual wall switch SG 10949.

FITTING

A. FITTING INFORMATION


For detailed fitting information, visit the Silent Gliss website.

Fixing points





B. CEILING FITTING

Clamp SG 3004




SG 3004
Clamp

Direct fitting (2C roller only)




SG 7002
Profile protector



SG 10865
Support plate


C. WALL FITTING

Smart Fix




Smart Fix SG 11200 - SG 11205 and bracket SG 3041:
Screw SG 10492 (M4x8) needed.


Smart Fix	X mm (SG 3041)	X mm (SG 3004)
SG 11200 / SG 11210	83	
SG 11201 / SG 11211	103	72
SG 11202 / SG 11212	123	92
SG 11203 / SG 11213	143	112
SG 11204 / SG 11214	173	142
SG 11205 / SG 11215	223	192
SG 11154	128-156	102-130
SG 11155	158-186	132-160
SG 11156	208-236	182-210




Smart Fix SG 11200 - SG 11205 and clamp SG 3004:
Screw SG 10074 (M4x8) needed.




Square Smart Fix SG 11210 - SG 11215 and bracket SG 3041:
Screw SG 10492 (M4x8) needed.




Square Smart Fix SG 11210 - SG 11215 and clamp SG 3004:
Screw SG 10074 (M4x8) needed.




Universal Smart Fix SG 11154 - SG 11156 and bracket SG 3041:
Screw SG 10407 (M4x10) needed.



Universal Smart Fix SG 11154 - SG 11156 and clamp SG 3004:
Screw SG 11158 (M4x12) needed.



SG 3004
Clamp



SG 3041
Bracket



SG 10074
Countersunk head screw
M4x8



SG 10407
Pan head screw M4x10




SG 10492

Pan head screw M4x8




SG 11158

Countersunk head screw M4x12




SG 11200

Smart Fix 60 mm




SG 11201

Smart Fix 80 mm




SG 11202

Smart Fix 100 mm




SG 11203

Smart Fix 120 mm




SG 11204

Smart Fix 150 mm




SG 11205

Smart Fix 200 mm




SG 11210

Square Smart Fix 60 mm




SG 11211

Square Smart Fix 80 mm




SG 11212

Square Smart Fix 100 mm




SG 11213

Square Smart Fix 120 mm




SG 11214

Square Smart Fix 150 mm




SG 11215

Square Smart Fix 200 mm




SG 11154

Universal Smart Fix 120 mm



SG 11155

Universal Smart Fix 150 mm




SG 11156


Universal Smart Fix 200 mm

D. RECESS FITTING


Recess profile SG 10862




One wedge SG 5118 per fixing point.
For detailed recess fitting, visit the Silent Gliss website.




SG 5118
Wedge



SG 10862
Recess profile




SG 10864
Recess mask




SG 11467
Recess mask

E. SUSPENDED FITTING

Hanger SG 6105




Curtain weight reduces by 30%.




SG 6105
Hanger with plate

V-hanger SG 6107




Curtain weight reduces by 30%.




SG 6107
V-Hanger with plate

SYSTEM OPTIONS


A. WAVE



SG 6365



SG 11466



SG 10852



SG 10854



SG 10856



SG 10867




SG 10886




SG 10887

Standard components:


- SG 6365 Wave hanger
- SG 11466 Wave end stop
- SG 10852 Wave 2C roller cord, 80 mm
- SG 10854 Wave overlap arm support
- SG 10856 Wave end stop, belt return
- SG 10867 Panhead screw
- SG 10886 Wave extension
- SG 10887 Wave overlap arm set




SG 10845




SG 10869



SG 10905



SG 10906




SG 10924

Optional components:


- SG 10845 Wave master carrier single stack 80 mm
- SG 10869 Wave 2C roller cord, 60 mm (no single stack)
- SG 10905 Wave glider cord, 80 mm
- SG 10906 Wave glider cord, 60 mm (no single stack)
- SG 10924 Wave glider support




SG 3582



SG 6349



SG 6363





SG 10075



SG 10076

Curtain components:

- SG 3582 Hook
- SG 6349 Wave curtain tape
- SG 6363 Wave top hemming tape
- SG 10075 Lead weight 50 gr/m
- SG 10076 Fabric weight



A = Stack depth
B = Stack size
C = Min. distance

Roller / glider cord SG 10852 / 10905	Pockets between hooks	Approx. curtain fullness	Stack depth A	Stack size B*	Min distance C
80	6	~2.1	140	210 per metre of track	90
80	7	~2.3	160	210 per metre of track	100

Roller / glider cord SG 10869 / 10906	Pockets between hooks	Approx. curtain fullness	Stack depth A	Stack size B*	Min distance C
60	4	~2.1	100	260 per metre of track	70
60	5	~2.3	120	260 per metre of track	80

*Stack size B plus 180 mm for each curtain stack!

MOTORS & CONTROLS

A. MOTOR FEATURES

Motors	SG 5190	SG 5192	SG 5193
--------	---------	---------	---------

Motor Features

Soft start / stop	•	•	•
Touch & Go	•	•	
Manual Override	•	•	•
Built-in receiver	•	•	
Electronic end-stop	•	•	•
Electronic revolution counter (unlimited revolution)	•	•	•
Parallel wiring possible without additional relays	•	•	•
Cable connectable with plug into motor		•	
IP class	IP 20	IP 20	IP 20


Control Features

Mains power control			•
Dry contact control	•	•	
Dry contact and / or SG Control A	•	•	
SG Control A	•	•	
Suitable for all common home automation systems (with suitable interface)	•	•	•

B. MOTOR
SPECIFICATIONS

Motors	Motor dimensions	Voltage	Current	Frequency	System speed / sec	Frequency receiver
SG 5190	L 293 x W 53 x D 68	100 - 240 V AC	0.8 - 0.4 A	50 / 60 Hz	15 cm / sec	433 MHz
SG 5192	L 293 x W 53 x D 68	24 V DC	3.5 A	n/a	15 cm / sec	433 MHz
SG 5193	L 293 x W 53 x D 68	100 - 240 V AC	0.8 - 0.4 A	50 / 60 Hz	15 cm / sec	n/a


C. MOTOR
DIMENSIONS



D. OPERATING
METHODS


See catalogue "controls" for details.

SG 5100B - Base




A: Motor SG 5190
B: Wall Switch SG 10949

SG 5100R - Remote




A: Motor SG 5190
B: Wall Switch SG 10949
C: Handset SG 10946

SG 5100T - Timer
Unit



A: Motor SG 5190
B: Wall Switch SG 10949
C: Timer Unit SG 11429

**SG 5100TC - Total
Control**



- A: Motor SG 5190
- B: Wall Switch SG 10949
- C: Timer SG 11429
- D: Handset SG 10946












**E. WIRING
DIAGRAMS**






Refer to Silent Gliss website.







PARTS
























A. STANDARD PARTS


	SG 3004 Clamp
	SG 3581 Hook
	SG 5190 Motor 100-240V AC, 1/130, radio receiver
	SG 10815 Cover
	SG 10819 Belt return
	SG 10821 Overlap arm
	SG 10822 Master carrier
	SG 10823 Belt connector arm
	SG 10824 Belt connector pin
	SG 10825 Belt
	SG 10826 Overlap arm support
	SG 10836 Mask pair stack
	SG 10837 Pilot runner
	SG 10838 Pilot runner

	SG 10840 2C roller
	SG 10850 Profile
	SG 10923 Pan head screw Freedriv M4x12
	SG 11464 Motor holder

B. OPTIONAL PARTS


	SG 3012 Hook
	SG 3041 Bracket
	SG 3582 Hook
	SG 3599 Hook
	SG 5118 Wedge
	SG 5192 Motor 24V DC, 1/130, radio receiver
	SG 5193 Motor 100-240V AC, 1/130, mains controlled
	SG 6004 Eyelet
	SG 6086 Spring stop
	SG 6105 Hanger with plate
	SG 6107 V-Hanger with plate
	SG 6349 Wave curtain tape
	SG 6363 Wave top hemming tape
	SG 6365 Wave hanger

	SG 7002 Profile protector		SG 10865 Support plate		SG 10951 Radio wall transmitter 5+1 channel
	SG 9959 Central control unit relay		SG 10867 Pan head screw Freedriv M4x16		SG 10952 Plug for dry contact RJ 12
	SG 10074 Countersunk head screw M4x8		SG 10869 Wave 2C roller cord 60 mm		SG 11127 Countersunk head screw M4x10
	SG 10075 Lead weight 50 g/m		SG 10886 Wave extension		SG 11154 Universal Smart Fix 120 mm
	SG 10076 Fabric weight		SG 10887 Wave extension		SG 11155 Universal Smart Fix 150 mm
	SG 10820 Overlap arm		SG 10905 Wave glider cord 80 mm		SG 11156 Universal Smart Fix 200 mm
	SG 10831 Connection bridge		SG 10906 Wave glider cord 60 mm		SG 11158 Countersunk head screw M4x12
	SG 10844 Wave end stop		SG 10924 Wave glider support		SG 11200 Smart Fix 60 mm
	SG 10845 Wave master carrier		SG 10927 Hook		SG 11201 Smart Fix 80 mm
	SG 10852 Wave 2C roller cord 80 mm		SG 10946 Radio hand held 1 channel		SG 11202 Smart Fix 100 mm
	SG 10854 Wave overlap plate		SG 10947 Radio hand held 2+1 channel		SG 11203 Smart Fix 120 mm
	SG 10856 Wave extension		SG 10948 Radio hand held 6+1 channel		SG 11204 Smart Fix 150 mm
	SG 10862 Recess profile		SG 10949 Radio wall transmitter 1 channel		SG 11205 Smart Fix 200 mm
	SG 10864 Recess mask		SG 10950 Radio wall transmitter 2 channel		SG 11210 Square Smart Fix 60 mm




SG 11211

Square Smart Fix 80 mm




SG 11212

Square Smart Fix 100 mm




SG 11213

Square Smart Fix 120 mm




SG 11214

Square Smart Fix 150 mm



SG 11215

Square Smart Fix 200 mm




SG 11295

End stop




SG 11429

Radio timer unit 1 channel




SG 11466

Wave end stop




SG 11467

Recess mask



SG 11963



Power supply set 24V/4A with GB plug



SG 11964

Power supply set 24V/4A with US plug

SG 5600



PRODUCT INFORMATION

- **Operation:** motorised
- **Range:** S - L
- **Fitting:** ceiling, wall, recess
- **Colours:** white RAL 9016, black RAL 9005 or anodised aluminum, special colours possible (recess profile only in white RAL 9016, black RAL 9005 or special color)
- **Fabrics:** refer to Silent Gliss fabric collection

Features:

- Quiet, fast and powerful motor
- 2-component (2C) roller technology
- Wave (2C)
- Various control options
- Touch & Go
- Manual override incl. permanent positioning sensor
- Easy programming
- 100-250 AC and / or 24 V DC in one motor
- Bendable
- Bendable recess profile
- UL version available

SYSTEM SPECIFICATIONS

A. SYSTEM DIMENSIONS



25 m



65 kg

Max. curtain weights with 2C rollers / Wave rollers

Up to 12 m: Touch & Go, manual override, auto programming mode


	2 m	4 m	6 m	8 m	10 m	12 m	15 m	18 m	21 m	25 m
	25	45	45	50	65	45	45	45	45	40
	25	45	45	50	65	45	45	45	45	40
	25	35	35	40	35	35	35	32	29	25
	25	35	35	40	35	35	35	32	29	25
	25	30	30	30	25	25	22	19	15	-
	25	30	30	30	25	25	22	19	15	-
	20	20	20	18	16	12	10	-	-	-
	20	20	20	18	16	12	10	-	-	-
(kg max.)										

Max. curtain weights with Wave gliders

	2 m	4 m	6 m	8 m	10 m
	20	25	25	25	20
	20	25	25	25	20
	20	20	20	20	15
	20	20	20	20	15
	20	20	20	15	10
	20	20	20	15	10
	20	20	15	8	-
	20	20	15	8	-
(kg max.)					


B. PROFILE

Profile and bending information



SG 10850

Profile




SG 10862

Recess profile



C. HOW TO MEASURE



A: System width
B: System height
C: Distance between floor and fabric

D. SPECIFICATION

TEXT

Silent Gliss SG 5600 Electrically Operated Curtain Track with Smart by Silent Gliss enabled motor. Comprises aluminium profile SG 10850 in [silver anodized / white powder coated / black powder coated] made-to-measure with motor SG 9060 with plug in smart module SG 11270. Includes internal drive belt SG 10825, belt return set SG 10819. Supplied with [2C rollers SG 10840 / Wave 2C glider cord 60mm SG 10906 / Wave 2C 80mm glider cord SG 10905 / 2C Wave roller glider cord 60mm SG 10869 / 2C Wave roller glider cord 80mm SG 10852]. Features 'Touch and Go' operation and manual override in the event of power failure. Fitted using [top fix clamps SG 3004 / face fix Smart Fix extension brackets]. Optional bendable recess profile SG 10862 in [white / black]. Operation by compatible third-party control system offering full two-way communication. Power only to be used in conjunction with associated 'Smart by Silent Gliss' Gateway and components. Motor SG 9060 is Matter enabled. All wiring to be strictly in accordance with Silent Gliss wiring diagrams.



Silent Gliss SG 5600 Electrically Operated Curtain Track. Comprises aluminium profile SG 10850 in [silver anodized / white powder coated / black powder coated] made-to-measure with motor SG 9060. Includes internal drive belt SG 10825, belt return set SG 10819. Supplied with [2C roller SG 10840 / Wave 2C glider cord 60mm SG 10906 / Wave 2C 80mm glider cord SG 10905 / 2C Wave roller glider cord 60mm SG 10869 / 2C Wave roller glider cord 80mm SG 10852]. Features 'Touch and Go' operation (with permanent power only) and manual override in the event of power failure. Fitted using [top fix clamps SG 3004 / face fix Smart Fix extension brackets]. Optional bendable recess profile SG 10862 in [white / black]. Powered by 24V DC power supply (not supplied) or mains power. Permanent memory limit switching positions. Operation by [mains switching / dry contact switching / radio control SG Control N / SG Control R]. Radio control requires additional plug-in module. Move App requires Move server SG 11900 and plug in module SG 11939. Motor SG 9060 is Matter enabled with SG 11939 plug in module. All wiring to be strictly in accordance with Silent Gliss wiring diagrams.

FITTING

A. FITTING INFORMATION

Fixing points



For detailed fitting information, visit the [Silent Gliss website](#).



Motor holder to be fixed (ceiling fitting only).



B. CEILING FITTING

Clamp SG 3004




SG 3004
Clamp

Direct fitting (2C roller only)




SG 7002
Profile protector




SG 10865
Support plate

C. WALL FITTING


Smart Fix




Smart Fix SG 11200 - SG 11205 and bracket SG 3041:
Screw SG 10492 (M4x8) needed.




Smart Fix SG 11200 - SG 11205 and clamp SG 3004:
Screw SG 10074 (M4x8) needed.




Square Smart Fix SG 11210 - SG 11215 and bracket SG 3041:
Screw SG 10492 (M4x8) needed.



Square Smart Fix SG 11210 - SG 11215 and clamp SG 3004:
Screw SG 10074 (M4x8) needed.




Universal Smart Fix SG 11154 - SG 11156 and bracket SG 3041:
Screw SG 10407 (M4x10) needed.




Universal Smart Fix SG 11154 - SG 11156 and clamp SG 3004:
Screw SG 11158 (M4x12) needed.

Smart Fix	X mm (SG 3041)	X mm (SG 3004)
SG 11200 / SG 11210	83	
SG 11201 / SG 11211	103	72
SG 11202 / SG 11212	123	92
SG 11203 / SG 11213	143	112
SG 11204 / SG 11214	173	142
SG 11205 / SG 11215	223	192
SG 11154	128-156	102-130
SG 11155	158-186	132-160
SG 11156	208-236	182-210



SG 3004
Clamp



SG 3041
Bracket



SG 10074
Countersunk head screw
M4x8




SG 10407
Pan head screw M4x10




SG 10492
Pan head screw M4x8




SG 11158
Countersunk head screw
M4x12




SG 11200
Smart Fix 60 mm




SG 11201
Smart Fix 80 mm




SG 11202
Smart Fix 100 mm




SG 11203
Smart Fix 120 mm




SG 11204
Smart Fix 150 mm




SG 11205
Smart Fix 200 mm




SG 11210
Square Smart Fix 60 mm




SG 11211
Square Smart Fix 80 mm




SG 11212
Square Smart Fix 100 mm




SG 11213
Square Smart Fix 120 mm




SG 11214
Square Smart Fix 150 mm




SG 11215
Square Smart Fix 200 mm



SG 11154
Universal Smart Fix 120 mm




SG 11155
Universal Smart Fix 150 mm




SG 11156
Universal Smart Fix 200 mm

D. RECESS FITTING


Recess profile SG 10862




One wedge SG 5118 per fixing point.
For detailed recess fitting, visit the Silent Gliss website.




SG 5118
Wedge



SG 10863
Recess mask




SG 10862
Recess profile




SG 10864
Recess mask

Motor recessed in suspended ceiling



Profile mounted with clamp SG 3004.

Access to the ceiling space is necessary for assembly / programming.




Profile SG 10862 recessed into ceiling.


Access to the ceiling space is necessary for assembly / programming.

E. SUSPENDED
FITTING

Hanger SG 6105




Curtain weight reduces by 30%.




SG 6105
Hanger with plate

V-hanger SG 6107




Curtain weight reduces by 30%.



SG 6107
V-Hanger with plate

SYSTEM OPTIONS


A. WAVE



SG 6365



SG 10844



SG 10852



SG 10854



SG 10856



SG 10867




SG 10886




SG 10887

Standard components:


- SG 6365 Wave hanger
- SG 10844 Wave end stop
- SG 10852 Wave 2C roller cord, 80 mm
- SG 10854 Wave overlap arm support
- SG 10856 Wave end stop, belt return
- SG 10867 Panhead screw
- SG 10886 Wave extension
- SG 10887 Wave overlap arm set




SG 10845




SG 10869



SG 10905



SG 10906




SG 10924

Optional components:


- SG 10845 Wave master carrier single stack 80 mm
- SG 10869 Wave 2C roller cord, 60 mm (no single stack)
- SG 10905 Wave glider cord, 80 mm
- SG 10906 Wave glider cord, 60 mm (no single stack)
- SG 10924 Wave glider support




SG 3582



SG 6349



SG 6363



SG 10075





SG 10076

Curtain components:

- SG 3582 Hook
- SG 6349 Wave curtain tape
- SG 6363 Wave top hemming tape
- SG 10075 Lead weight 50 gr/m
- SG 10076 Fabric weight

Wave stack depth - 2C roller / glider cord (standard components)



A = Stack depth
B = Stack size
C = Min. distance

Roller / glider cord SG 10852 / 10905	Pockets between hooks	Approx. curtain fullness	Stack depth A	Stack size B*	Min distance C
80	6	~2.1	140	210 per metre of track	90
80	7	~2.3	160	210 per metre of track	100

Roller / glider cord SG 10869 / 10906	Pockets between hooks	Approx. curtain fullness	Stack depth A	Stack size B*	Min distance C
60	4	~2.1	100	260 per metre of track	70
60	5	~2.3	120	260 per metre of track	80

*Stack size B plus 190 mm for each curtain stack!

MOTOR & CONTROLS

A. MOTOR FEATURES

Motor	SG 9060
-------	---------

Motor Features

Soft start / stop	•
Touch & Go	•
Manual Override	•
Modular radio system (optional)	•
Electronic end-stop	•
Electronic revolution counter (unlimited revolution)	•
Parallel wiring possible without additional relays	•
High-end DC motor with brushless technology	•
Permanent positioning sensor (even without power)	•
100 - 250 V AC and / or 24 V DC in one motor	•
Cable connectable with plug into motor	•
IP class	IP 40


Control Features

Mains power control	•
Dry contact control	•
Dry contact and / or SG Control N (with radio module)	•
Dry contact and / or SG Control R (with radio module)	•
SG Control N (with radio module)	•
SG Control R (with radio module)	•
Smart by Silent Gliss (with smart module)	•
Suitable for all common home automation systems (with suitable interface)	•
Compatible with Matter (with radio module)	•

B. MOTOR SPECIFICATIONS

Motor	Motor dimensions	Voltage AC	Voltage DC	Current	Frequency	System speed / sec	Frequency receiver
SG 9060	L 206 x W 60 x D 96	100 - 250 V AC	24 V DC	1.3 - 0.5 A	50 - 60 Hz	21 cm / sec	n/a
SG 9060 w/ SG Control N	L 226 x W 60 x D 96	100 - 250 V AC	24 V DC	1.3 - 0.5 A	50 - 60 Hz	21 cm / sec	433 MHz
SG 9060 w/ SG Control R	L 226 x W 60 x D 96	100 - 250 V AC	24 V DC	1.3 - 0.5 A	50 - 60 Hz	21 cm / sec	433 MHz
SG 9060 w/ Smart by SG	L 226 x W 60 x D 96	100 - 250 V AC	24 V DC	1.3 - 0.5 A	50 - 60 Hz	21 cm / sec	Smart by SG

C. MOTOR DIMENSIONS / MODULES



Motor SG 9060 can be equipped with following modules:

- SG 11939 Radio module SG Control N (Matter compatible)
- SG 11411 Radio module SG Control R
- SG 11270 Smart module

See catalogue "controls" for details.

D. OPERATING METHODS

See catalogue "controls" for details.

Wall switch



System can be operated by fixed wall switch.

SG Control N



Various radio hand-held and wall transmitters available. Radio module SG 11939 is Matter compatible.



Silent Gliss Move App.

SG Control R



Various radio hand-held and wall transmitters available.

Smart by Silent Gliss



Open designed two-way communication system which allows to flawlessly integrate products with most major building management systems. Smart module SG 11270 required.














E. WIRING
DIAGRAMS








Refer to Silent Gliss website.











PARTS








































A. STANDARD PARTS



















	SG 3004 Clamp
	SG 9060 Motor 100-250V AC & 24V DC
	SG 9917 Hirschmann portable socket-outlet STAK 3 N
	SG 10725 Programming distance holder
	SG 10815 Cover
	SG 10816 Cover
	SG 10819 Belt return
	SG 10821 Overlap arm
	SG 10822 Master carrier
	SG 10823 Belt connector arm
	SG 10824 Belt connector pin
	SG 10825 Belt
	SG 10826 Overlap arm support
	SG 10836 Mask pair stack

	SG 10837 Pilot runner
	SG 10838 Pilot runner
	SG 10840 2C roller
	SG 10850 Profile
	SG 10923 Pan head screw Freedriv M4x12
	SG 11909 Motor holder

B. OPTIONAL PARTS

	SG 3041 Bracket
	SG 3582 Hook
	SG 5118 Wedge
	SG 6086 Spring stop
	SG 6105 Hanger with plate
	SG 6107 V-Hanger with plate
	SG 6349 Wave curtain tape
	SG 6363 Wave top hemming tape
	SG 6365 Wave hanger
	SG 6794 Pan head screw 2.9x38 DIN 7981C
	SG 7002 Profile protector
	SG 9916 Hirschmann plug set
	SG 9959 Central control unit relay
	SG 10074 Countersunk head screw M4x8

	SG 10075 Lead weight 50 g/m		SG 10864 Recess mask		SG 11201 Smart Fix 80 mm
	SG 10076 Fabric weight		SG 10865 Support plate		SG 11202 Smart Fix 100 mm
	SG 10293 Cable 230V AC, 2/3/5/10 m		SG 10867 Pan head screw Freedriv M4x16		SG 11203 Smart Fix 120 mm
	SG 10714 Plug 6-pin, MC 1.5/6-ST-3.81		SG 10869 Wave 2C roller cord 60 mm		SG 11204 Smart Fix 150 mm
	SG 10820 Overlap arm		SG 10886 Wave extension		SG 11205 Smart Fix 200 mm
	SG 10831 Connection bridge		SG 10887 Wave extension		SG 11210 Square Smart Fix 60 mm
	SG 10844 Wave end stop		SG 10905 Wave glider cord 80 mm		SG 11211 Square Smart Fix 80 mm
	SG 10845 Wave master carrier		SG 10906 Wave glider cord 60 mm		SG 11212 Square Smart Fix 100 mm
	SG 10851 2 m cable UL certified incl. plug only for USA		SG 10924 Wave glider support		SG 11213 Square Smart Fix 120 mm
	SG 10852 Wave 2C roller cord 80 mm		SG 11154 Universal Smart Fix 120 mm		SG 11214 Square Smart Fix 150 mm
	SG 10854 Wave overlap plate		SG 11155 Universal Smart Fix 150 mm		SG 11215 Square Smart Fix 200 mm
	SG 10856 Wave extension		SG 11156 Universal Smart Fix 200 mm		SG 11260 Gateway Cedia
	SG 10862 Recess profile		SG 11158 Countersunk head screw M4x12		SG 11261 Gateway KNX
	SG 10863 Recess mask		SG 11200 Smart Fix 60 mm		SG 11262 Expansion unit

	SG 11264 Power supply 24V DC, 3.8A DIN Rail		SG 11936 Radio wall transmitter 1 channel
	SG 11265 Power supply 24V DC, 5A DIN Rail		SG 11937 Radio wall transmitter 6 channel
	SG 11266 Power supply 24V DC, 10A DIN Rail		SG 11939 Radio modul control N
	SG 11270 Smart module		SG 11963 Power supply set 24V/4A with GB plug
	SG 11281 Cabinet for 8 systems		SG 11964 Power supply set 24V/4A with US plug
	SG 11282 Cabinet for 24 systems		SG 20336 Hand held transmitter 8 channel
	SG 11283 Cabinet for 56 systems		SG 20913 Wall switch single channel
	SG 11295 End stop		SG 20914 Wall switch 8 channel
	SG 11318 Plug 4-pin, MC 1.5/4-ST-3.5		SG 20917 Pattress box
	SG 11325 Smart plug 6-pin, MC 1.5/6 ST-3.81		
	SG 11411 Radio module type R		
	SG 11900 Move Server		
	SG 11931 Radio hand held 1 channel		
	SG 11932 Radio hand held 6 channel		

The Architects of Silence

Silent Gliss is the leading global supplier of premium interior window treatments. Since 1952 we have been tirelessly committed to the development of the world's smoothest, quietest systems using state of the art technology.

Driven by customer needs, Silent Gliss offers functional and durable products. Expert technical advice coupled with installation and support services complete the offer. Silent Gliss stands for innovative, sustainable, tailor made solutions, exceptional design and first-class quality.

Silent Gliss Ltd.

Pyramid Business Park
Poorhole Lane, Broadstairs
Kent CT10 2PT
United Kingdom
T +44 1843 863571
F +44 1843 864503
info@silentgliss.co.uk

Silent Gliss Global Ltd.

Pyramid Business Park
Poorhole Lane, Broadstairs
Kent CT10 2PT
United Kingdom
T +44 1843 874250
F +44 1843 864503
info@silentglissglobal.com

Silent Gliss Blinds Trading LLC

Office 1906
The H Hotel Complex
Trade Center First
Dubai
United Arab Emirates
T +971 4 7050318
info@silentgliss.ae

silentgliss.co.uk
silentglissglobal.com
silentgliss.ae